HD 6/15 C

Unheated high-pressure cleaner for daily commercial use. Thanks to the compact dimensions, robust construction style and maximum manoeuvrability, this machine from the compact class is true to its name.

1 Easy Press spray gun

- Ergonomic design for convenient operation.
- Reduced operation and holding effort for easy operation.

2 Infinitely variable pressure and water flow regulation

- Adjustable directly on the machine.
- For gentle cleaning of sensitive surfaces.

3 Extendable push handle

- Large aluminium profiles ensure stability and easy turning manoeuvre.
- Acts as an accessory holder when extended.

4 Outstanding mobility

- For fast cleaning at different locations of use.
- Space-saving storage in service vehicles.

HD 6/15 C, 1.150-600.0, 2015-02-04

Technical Data and Equipment.

HD 6/15 C

- Three-piston axial pump with ceramic pistons
- Easy Press spray gun with soft grip surface
- Variable pressure

Technical data

Order No.		1.150-600.0
EAN code		4039784717374
Current type	**Ph / V / Hz**	1 / 230 / 50
Flow rate	**l/h**	230–560
Working pressure	**bar / MPa**	30–150 / 3–15
Max. pressure	**bar / MPa**	190 / 19
Max. feed temperature	**°C**	60
Connected load	**kW**	3.1
Weight	**kg**	23
Dimensions (L x W x H)	**mm**	360 × 375 × 925

Equipment

Spray gun		Easy-press trigger gun
Spray gun with soft grip		■
High-pressure hose	**m**	10 / Premium quality
Spray lance	**mm**	850
Triple nozzle (0°/25°/40°)		Manual
Anti-twist system		■
Pressure cut-off		■

■ **Included in delivery.**

HD 6/15 C, 1.150-600.0, 2015-02-04

Accessories for HD 6/15 C 1.150-600.0

1

2–3

5–7, 11

8, 10

9

12

13–14

15

16

17–20

		Order No.	ID	Max. working pressure	Length		Price	Description	
Standard with unions on both sides									
High-pressure hose, 15 m, ID 8, 315 bar, including rotary coupling	1	6.390-010.0	ID 8	315 bar	15 m				▲
High-pressure hose, 20 m, ID 8, 315 bar, extension piece	2	6.390-031.0	ID 8	315 bar	20 m				▲
High-pressure hose, 15 m, ID 10, 220 bar, extension piece	3	6.390-023.0	ID 10	220 bar	15 m				▲
High-pressure hose, 10 m, ID 8, 315 bar, extension piece	4	6.391-342.0	NW 8	315 bar	10 m				▲
High-pressure hose, 30 m, ID 8, including rotary coupling	5	6.390-293.0	ID 8	315 bar	30 m				▲
Longlife 400 with unions on both sides									
High-pressure hose Longlife 400, 10 m, ID 8, including rotary coupling	6	6.388-083.0	ID 8	400 bar	10 m			10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 x 1.5, with kink protection.	▲
High-pressure hose Longlife 400, 20 m, ID 8, extension	7	6.390-027.0	ID 8	400 bar	20 m			with rotary coupling, 2 x M 22 x 1.5	▲
High pressure hose ID 6, 10 m, including rotary coupling	8	6.391-883.0	ID 6	400 bar	10 m			With rotary coupling, 2 x M 22 x 1,5	▲
Longlife 400 high-pressure hose, 10 m, DN 8, extension piece	9	6.391-354.0	ID 8	400 bar	10 m				▲
High-pressure hose Longlife 400, 15 m, ID 8, including rotary coupling	10	6.389-709.0	ID 8	400 bar	15 m			With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 30 m, ID 8, including rotary coupling	11	6.390-294.0	ID 8	400 bar	30 m				▲
High-pressure hose 1.5 m, ID 8, including connectors	12	6.390-178.0	ID 8	400 bar	1.5 m			1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	□
Food industry version with unions on both sides									
High-pressure hose, 10 m, DN 8, suitable for the food industry, extension piece	13	6.389-479.0	ID 8	250 bar	10 m			10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	▲
High-pressure hose, 20 m, ID 8, suitable for food industry, extension piece	14	6.389-581.0	ID 8	250 bar	20 m			20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	▲
Longlife food design with screw connections at both ends									
High pressure hose food ID 8, 10 m	15	6.391-864.0	ID 8	400 bar	10 m			Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5	▲
High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling	16	6.391-887.0	ID 8	400 bar	20 m				▲
Standard									
High-pressure hose, 10 m, ID 6, AVS trigger gun connector	17	6.391-238.0	ID 6	250 bar	10 m			10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.	■
High-pressure hose, 15 m, ID 6, AVS gun connection	18	6.391-394.0	ID 6	250 bar	15 m				□
High-pressure hose, 10 m, ID 8, AVS trigger gun connector	19	6.390-025.0	ID 8	315 bar	10 m			10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	□
High-pressure hose, 15 m, ID 8, AVS trigger gun connector	20	6.390-185.0	ID 8	315 bar	15 m			15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C
1.150-600.0

21–22

23

24

25

26

27

		Order No.	ID	Max. working pressure	Length		Price	Description	
High-pressure hose, 20 m, ID 8, AVS trigger gun connector	21	6.390-171.0	ID 8	315 bar	20 m			20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	□
High-pressure hose, 10 m, ID 6, 300 bar, AVS trigger gun connection	22	6.391-875.0	ID 6	300 bar	10 m			With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar	□
Longlife 400									
Longlife 400 high-pressure hose, 10 m, DN 6, M 22 x 1.5	23	6.391-882.0	ID 6	400 bar	10 m			With patented AVS connection in the trigger gun (pivot-mounted).	□
Longlife 400 high-pressure hose, 10 m, DN 8,	24	6.391-351.0	NW 8	400 bar	10 m				□
Food industry version									
High-pressure hose, 15 m, ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey	25	6.391-654.0	ID 6	250 bar	15 m			15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.	□
Longlife food design									
HIgh-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun connection	26	6.391-888.0	ID 6	400 bar	15 m			Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	□
Special hoses									
High-pressure hose 1.5 m, ID 8, including connectors, outlet bend	27	6.388-886.0	ID 8	400 bar	1.5 m				□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C
1.150-600.0

1

2

3

4

5

		Order No.	Flow rate				Price	Description	
Easy Press high-pressure trigger gun with holding force reduction (Kärcher patent)									
Easy Press HP trigger gun with soft grip	1	4.775-463.0						Easy press high-pressure trigger gun with softgrip. For high-pressure hoses DN 6 and DN 8 with 11 mm swivel diameter.	■
Trigger guns									
High-end HP trigger gun	2	4.775-823.0							□
Inaktiv									
High-end HP trigger gun	3	4.775-804.0							□
Quick connect									
Quick coupling	4	6.401-458.0						For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female.	□
Male coupling	5	6.401-459.0						Hardened stainless steel nipple for quick coupling 6.401-458. With M22 x 1,5 male.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C
1.150-600.0

1

2

3

4

		Order No.	Max. working pressure	Nozzle size			Price	Description	
Triple nozzles									
Triple nozzle 034	1	4.767-147.0	300 bar	34				Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.	■
Triple nozzle, touchless changeover									
Triple nozzle, touchless changeover	2	4.767-001.0		34				Triple nozzle with high-pressure pencil jet (25°) and low-pressure fan jet (40°). Fast and easy jet changeover by turning the nozzle.	□
Dirt Blaster, small									
Dirt blaster	3	4.767-022.0	180 bar	35				Small rotary nozzle for dirt blaster. The rotating point jet achieves 10 times the cleaning performance. Outstanding working time thanks to ceramic nozzle and bearing ring. Max. 180 bar/18 MPa, 60°C.	□
Dirt blaster, large									
Dirt blaster – without changeover function	4	4.763-931.0	300 bar	35				The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C 1.150-600.0

1, 6

2

3

4

5

7–8

9

10

11

12

13

14

15

16

		Order No.	Max. working pressure	Length			Price	Description	
Inaktiv									
Spray lance, 2,050 mm, swivelling, ergonomical	1	4.760-366.0	300 bar	2050 mm				Spray lance, 2,050 mm, swivelling, ergonomical	□
Rotating spray lances									
850 mm spray pipe, rotatable	2	4.760-663.0	300 bar	850 mm				850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	■
600 mm spray pipe, rotatable	3	4.760-664.0	300 bar	600 mm				600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
1050 mm spray pipe, rotatable	4	4.760-660.0	300 bar	1050 mm				1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
1550 mm spray pipe, rotatable	5	4.760-661.0	300 bar	1550 mm				1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
2050 mm spray pipe, rotatable	6	4.760-662.0	300 bar	2050 mm				2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Variable pressure spray lance									
Variable pressure spray lance	7	4.760-362.0		670 mm				670 mm variable pressure lance with integrated pressure gauge. Variable pressure adjustment on the handle. Nozzle connector: M 24 x 1.5. Low pressure detergent application.	□
Variable pressure lance	8	4.760-230.0		1040 mm				1040 mm pressure adjustable lance with integrated pressure gauge. Variable pressure adjustment on the handle. Nozzle connector: M 24 x 1.5. Low pressure detergent application.	□
Adapter for variable pressure spray lance									
Adapter for variable pressure lance	9	4.762-075.0						For items 4.760-230 and 4.760-362 for mounting accessories to lance, M 24/18 x 1.5	□
Angular spray lance									
Spray lance for toilets and rain gutters	10	4.760-073.0						Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	□
Undercarriage spray lance									
Underbody lance	11	4.760-245.0		700 mm				Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	□
Spray lances									
Vibrasoft lance	12	6.415-951.0	250 bar	950 mm				The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden on the user, e.g. when working with the dirt blaster.	□
Spray lance									
250 mm lance, non-rotatable	13	4.760-667.0		250 mm				250 mm stainless steel lance. With manual coupling. Non-rotatable.	□
Double lance									
Double lance 960 mm	14	6.394-665.0	310 bar	960 mm				960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	□
Flexible spray lance									
Flexible lance 1050 mm	15	6.394-654.0	210 bar	1050 mm				1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	□
Telescopic spray lance									
Telescopic spray pipe	16	6.394-690.0	225 bar						□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C 1.150-600.0

18

		Order No.	Max. working pressure	Length			Price	Description	
Strap for telescopic spray pipe	17	6.373-987.0						Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.	□
Gutter cleaner									
Gutter cleaning lance	18	2.642-305.0						The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C
1.150-600.0

1

2


3

4

6, 15

7

8

9–13

14

		Order No.	Flow rate	Nozzle size	Diame-ter		Price	Description	
Hard surface cleaner FR 30									
Hard surface cleaner FR 30	1	2.642-997.0			300 mm				□
FR 30 Me surface cleaner									
Hard surface cleaner FR 30 Me	2	2.640-355.0			300 mm			Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	□
Machine-specific nozzle kits for FR									
Nozzle kit for surface cleaners	3	2.640-401.0	500–650 l/h					Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	□
Hard surface cleaner FRV 30									
FRV 30 surface cleaner	4	2.642-999.0							□
Rubber lip for FRV 30	5	2.642-910.0						For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	□
Extension hose 5 m	6	4.440-939.0						5m extension hose for FRV 30. Connection sleeve included.	□
ABS hose fastening	7	2.642-528.0							□
ABS dirt trap	8	2.642-532.0							□
Machine-specific nozzle kits for FRV									
Nozzle kit 035 – for FRV 30	9	2.642-430.0		35					□
Nozzle kit 040 – for FRV 30	10	2.642-431.0		40					□
Nozzle kit 045 – for FRV 30	11	2.642-432.0		45					□
Nozzle kit 050 – for FRV 30	12	2.642-433.0		50					□
Nozzle kit 080 – for FRV 30	13	2.642-982.0		80					□
FRV 30 Me surface cleaner									
FRV 30 Me	14	2.642-911.0							□
FRV 30 Me extension hose	15	4.441-040.0							□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C 1.150-600.0

1

2

		Order No.	Nozzle size				Price	Description	
Power nozzle spray angle 25°									
Power nozzle spray angle 25°	1	2.883-803.0	34					Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	□
25° power nozzle for applying cleaning agent	2	2.884-521.0	250						□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C
1.150-600.0

1

2

5

6

7

8

9

10

		Order No.					Price	Description	
Coupling									
Coupling	1	4.403-002.0						Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	□
Connector									
Nozzle screws / screw socket	2	4.402-022.0						Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	□
Cleaning agent injector									
Injector complete HD 6/15C	3	6.645-758.0							□
Add-on kit proportioning valve	4	6.500-000.0							□
Cleaning agent injector for high pressure (without nozzle)	5	3.637-170.0						Cleaning agent dosage at high pressure 3 - 5 %	□
Machine-specific nozzle kit with order no. 3.637-170.0									
Machine-specific nozzle kit with order no. 3.637-170.0, HP 500–700 l/h	6	4.769-045.0						For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union	□
Nozzle union									
Nozzle connector	7	5.401-210.0						For protecting and connecting Kärcher power nozzles to spray lances (M 18 x 1.5 IG).	□
Spacer (including nozzle union)									
Spacer (includes nozzle screws)	8	5.394-294.0						Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.	□
Rotary coupling									
Rotary coupling	9	4.401-091.0						Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	□
Adapters									
Adapter M 22 – Swivel	10	4.424-004.0						M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C 1.150-600.0

1–2

3

4

		Order No.	Nozzle size				Price	Description	
Wet blasting attachment (without nozzle)									
Wet blasting attachment with flow control (without nozzles)	1	4.762-010.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	□
Wet blasting attachment without flow control (nozzles not included)	2	4.762-022.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	□
Nozzle kits for wet jet unit									
Nozzle kit for wet jet unit 035	3	2.638-526.0	35					Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.	□
Boron carbide nozzle									
Boron carbide nozzle, for machines up to 1,000 l/h	4	6.415-084.0	6 mm					In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C
1.150-600.0

1–2

3

4–6

7

		Order No.	Max. working pressure	Nozzle size	Diame-ter		Price	Description	
Pipe cleaning hose, ID 6									
Pipe cleaning hose, NW 6, 20 m	1	6.390-028.0	120 bar					The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	□
Pipe cleaning hose, ID 6, 30 m	2	6.390-029.0	120 bar					30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	□
Pipe cleaning nozzle									
Rotating pipe cleaning nozzle	3	6.415-428.0		50	16 mm			Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.	□
Pipe cleaning dirt blaster D 25 / 040	4	6.415-944.0		40	25 mm			The forward-tilted rotating pencil jet removes the most stub-born dirt. The three backwards-tilted jets ensure the neces-sary forward movement, as well as convenient handling.	□
Pipe cleaning dirt blaster D 30 / 040	5	6.415-946.0		40	30 mm				□
Pipe cleaning dirt blaster D 35 / 040	6	6.415-948.0		40	35 mm				□
Barrel and tank cleaning									
Barrel cleaner – BC 14/12	7	2.641-740.0	120 bar					The BC 14/12 is an spray system for the efficient interior cleaning of containers and barrels##, specially oak barrels with a volume of between 225 and 600 litres. One cleaning cycle is completed within 36 seconds and every spot in the container is covered by a water jet. After cleaning is finished the BC 14/12 can easily and conveniently take up the dirty water. The transformer included with the BC 14/12 makes it possible to use it worldwide (110 - 240 V, 50 - 60 Hz). The nozzle kits included make possible use with high-pressure cleaners with a water volume of 600 to 1400 l / h. Electrical components are protected in accordance with IP 55.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C
1.150-600.0

1

2

3

4

5

		Order No.	Flow rate				Price	Description	
Inno Foam Kit									
Inno Foam Set with detergent injector	1	2.640-151.0						High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	□
Easy Foam Set									
Easy Foam Set with RM injector	2	2.640-691.0						HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	□
Nozzle kits for Inno/Easy Foam Set									
Nozzle kit 055 for Inno / Easy Set 500–600 l/h	3	2.640-870.0	500–600 l/h					Optimal adaptation to different machine outputs for economic use.	□
Foam nozzle mounting kit									
Foam nozzle attachment kit	4	2.637-926.0						Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	□
Cup foam lance									
Cup foam lance	5	6.394-668.0	1200 l/h					Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.	□
1-litre cleaning agent container for foam lance	6	6.414-954.0							□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C
1.150-600.0



		Order No.	Length				Price	Description	
Automatic, self-winding hose reels									
Automatic hose reel, coated	1	2.639-919.0	20 m					Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	☐
Powder-coated swivel holder	2	2.639-931.0						Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	☐
Automatic hose reel, stainless steel, includes swivel holder	3	6.391-421.0	20 m					Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	☐
Automatic hose reel, powder-coated steel / plastic	4	6.392-975.0	20 m					Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	☐
Automatic stainless steel / synthetic material hose drum	5	6.392-965.0	20 m					Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	☐
ABS automatic stainless steel hose drum	6	2.641-866.0	20 m					High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrossion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	☐
ABS pivoting stainless steel wall bracket	7	2.641-867.0						Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	☐

■ Included in delivery. ☐ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C
1.150-600.0

1

2–4

5

6

7

8

9

10

		Order No.	Length	Diameter			Price	Description	
Starting current limiter									
Starting current limiter	1	2.637-495.0						Reduces starting current in single-phase supply and protects line fuse.	□
Geka coupling									
Geka connector with hose barb, R 1/2"	2	6.388-461.0						with hose liner	□
Geka connector with hose barb, R 3/4"	3	6.388-455.0							□
Geka connector with inner thread, R 3/4"	4	6.388-473.0						with female thread	□
Suction filter									
Suction filter with check valve	5	4.730-012.0						Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	□
Water suction filter	6	6.414-956.0							□
Water fine filter									
Water fine filter, with adapter	7	4.730-102.0						Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	□
Water supply hose									
Water supply hose	8	4.440-038.0	7.5 m					NW 13 R1" / R 3/4", up to 30 °C	□
	9	4.440-207.0	7.5 m					NW 19 R1" / R 3/4", up to 85 °C, for pick-up	□
Backflow check valve									
Backflow preventer	10	2.641-374.0						To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 6/15 C 1.150-600.0

1–2

3

4

		Order No.	Flow rate				Price	Description	
Rotating washing brush									
Rotating wash brush for < 800 l/h machines, natural hair bristles	1	4.762-560.0	500–800 l/h						□
Rotating wash brush for < 800 l/h machines, nylon bristles	2	4.762-561.0	500–800 l/h					The rotating wash brush gently removes fine dust and grime from all surfaces. Heat-resistant up to 80°C. (M 18 x 1.5, replaceable brush insert).	□
Push-on washing brush									
Push-on washing brush	3	4.762-016.0						Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	□
Push-on wash brush	4	4.762-497.0						The wash brush is fitted directly onto the devices' new dual and triple nozzles using clamping.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.